

Alta LED Flush Mount AAF Series

Features

Low profile design with edge-lit light panel construction. Ideal use in kitchens, hallways, and anywhere general lighting is needed. Provides lighting in residential, commercial and hospitality applications. Fixture mounts to standard junction box (not included).

Construction

Housing is die-formed steel. Standard mounting holes and hardware included. Power supply connections must be made inside junction box (not included).

Finish

Painted Black/Chrome or Satin Nickel/White finish combinations.

Diffuser

White acrylic.

Electrical

D1 Driver

Input 120 VAC, 60 Hz. The LED driver is dimmable with a 2-wire (TRIAC) or electronic low voltage (ELV) dimmer switch.

D2 Driver

Input 120-277 VAC 60 Hz. LED driver is dimmable 0-10V DC.

LED

Integrated LED modules capable of producing: 17.5W = 1400 source lumens, 740 delivered lumens 35W = 2600 source lumens, 1280 delivered lumens 3000K (CCT). Rated for 50,000 Hrs. 90 CRI.


Certification

All fixtures are cETLus listed for indoor damp locations.

Warranty

Limited warranty: This fixture is free from defects in materials and workmanship for a period of 5 years from date-of-purchase.

Specifications and dimensions subject to change without notice.









Black/Chrome



Satin Nickel/White





Ordering Information:

			Source	Delivered			
Black/Chrome	Satin Nickel/White	LED	Lumens	Lumens	CCT	DIA.	D
AAF121400L30D1BKPC	AAF121400L30D1SNWH	17.5W	1400	740	3000K	12"	2"
AAF121400L30D2BKPC	AAF121400L30D2SNWH	17.5W	1400	740	3000K	12"	2"
AAF162600L30D1BKPC	AAF162600L30D1SNWH	35W	2600	1280	3000K	16"	2"
AAF162600L30D2BKPC	AAF162600L30D2SNWH	35W	2600	1280	3000K	16"	2"