

Anton LED Pendant ANP Series

Features

This modern double layer drum design provides a dramatic look and features Lumafuse™ laminated fabric/acrylic shade in 2 colors. White bottom acrylic diffuser disperses the light. Suspended with a 3 ft. adjustable rigid stem expandable up to 9 ft.

Construction

Metal housing and canopy. The canopy fits over a standard junction box. Power supply connections must be made inside a junction box (not included).

Finish

Stamped metal components are paintable white baked gloss enamel.

Diffuse

Utilizing Lumafuse $^{\text{TM}}$ laminated fabric to acrylic in Jute or Linen White. Matte white acrylic bottom diffuser.

Electrical

Input 120-277 VAC 60 HZ.

Compatible with residential (TRIAC/ELV) and commercial (0-10V) dimmers. TRIAC and ELV dimming only at 120 VAC.

LED

Integrated LED modules capable of producing:

12" - 18W = 1400 source lumens 15" - 30W = 2400 source lumens

19" - 42W = 3200 source lumens

Adjustable Choice 3000K, 3500K, 4000K (CCT).

Rated for 50,000 Hrs., 90 CRI

Certification

All fixtures are cETLus listed for indoor damp locations. *Title 24/JA8 Compliant

Warranty

Limited warranty: This fixture is free from defects in materials and workmanship for a period of 5 years from date-of-purchase.

Specifications and dimensions subject to change without notice.
















Ordering Information:

| | | | Source | | | | |
|-------------------|--------------------|-----|--------|-------------------|---------|--------|--|
| Jute | Linen White | LED | Lumens | Adjustable CCT | DIA. | Н | |
| ANP1214LAJUDSN-JT | ANP1214LAJUDSN-LW | 18W | 1400 | 3000K/3500K/4000K | 12-1/4" | 4-3/4" | |
| ANP1524LAJUDSN-JT | *ANP1524LAJUDSN-LW | 30W | 2400 | 3000K/3500K/4000K | 15" | 5-1/2" | |
| ANP1932LAJUDSN-JT | *ANP1932LAJUDSN-LW | 42W | 3200 | 3000K/3500K/4000K | 19-1/4" | 5-1/2" | |