

Arlo LED Sconce ARLS Series

Features

Modern geometric design with a frosted acrylic diffuser. Ideal use in hallways, entrances or anywhere general lighting is needed. Provides lighting in residential, commercial and hospitality applications. Meets ADA requirements. Fixture mounts to standard junction box (not included).

Construction

Back plate is die-formed of 22-gauge steel. Standard mounting holes and hardware are included. Power supply connections must be made inside a junction box (not included).

Finish

Backplate is finished in Satin Nickel.

Diffuser

Diffuser is made from a thick frosted acrylic.

Electrical

D1 - Input 120 VAC / 60Hz.
MV - Input 120-277 VAC/ 60 Hz.
Compatible with residential TRIAC and ELV dimmers (D1 ONLY).

Lamping

Fixture includes a LED modules capable of producing: 10W, 1000 source lumens, 710 delivered lumens 3500K (CCT). Rated for 50,000 Hrs. 90 CRI.

Certification

All fixtures are cETLus listed for indoor damp locations. ADA ENERGY STAR®*
Title 24/JA8 Compliant**

Warranty

Limited warranty: This fixture is free from defects in materials and workmanship for a period of 5 years from date of purchase.

Specifications and dimensions subject to change without notice.

Ordering Information:

			Delivered				
Satin Nickel	LED	Lumens	Lumens	CCT	H	W	D
ARLS050407L35D1SN**	10W	1000	710	3500K	5"	4-5/8"	3-1/2"
ARLS050407L35MVSN*	10W	1000	710	3500K	5"	4-5/8"	3-1/2"

LOCATION	DATE
PREPARED BY	QUANTITY
COMMENTS	FIXTURE TYPE
CATALOG NUMBER	













