

Arlo LED Vanity ARLV Series

Features

LED contemporary style. Satin nickel finish with frosted acrylic diffusers provide a modern geometric design to this vanity. Provides lighting in residential, commercial and hospitality applications. Fixture mounts to standard junction box (not included).

Construction

Back plate is die-formed of 22-gauge steel. Standard mounting holes and hardware are included. Power supply connections must be made inside a junction box (not included).

Finish

All exposed metal is finished in Satin Nickel.

Diffuser

Diffusers are made from a thick frosted acrylic.

Electrical

D1 - Input 120 VAC / 60Hz.
MV - Input 120-277 VAC/ 60 Hz.
Compatible with residential TRIAC and ELV dimmers (D1 ONLY).

LED

Integrated LED modules capable of producing: 30W = 3000 source lumens, 2200 delivered lumens 40W = 4000 source lumens, 2850 delivered lumens 3500K (CCT). Rated for 50,000 Hrs. 90 CRI.

Certification

All fixtures are cETLus listed for damp indoor locations. ADA ENERGY STAR®*
Title 24/JA8 Compliant**

Warranty

Limited warranty: This fixture is free from defects in materials and workmanship for a period of 5 years from date-of-purchase.

Specifications and dimensions subject to change without notice.

Ordering Information:

		Source	Delivered				
Satin Nickel	LED	Lumens	Lumens	CCT	L	Н	D
ARLV250418L35D1SN (3-Light)**	30W	1800	2200	3500K	25"	4"	3-3/4"
ARLV250418L35MVSN (3-Light)*	30W	1800	2200	3500K	25"	4"	3-3/4"
ARLV330424L35D1SN (4-Light)**	40W	2400	2850	3500K	33"	4"	3-3/4"
ARLV330424L35MVSN (4-Light)*	40W	2400	2850	3500K	33"	4"	3-3/4"

LOCATION	DATE
PREPARED BY	QUANTITY
COMMENTS	FIXTURE TYPE
CATALOG NUMBER	















