



LOCATION		DATE
PREPARED BY		QUANTITY
COMMENTS		FIXTURE TYPE
CATALOG NUMBER		

Ash LED Flush Mount ASHF Series

Features

Decorative perforated metal ring with edge-lit panel construction. Ideal use in kitchens, hallways, and anywhere general lighting is needed. Provides lighting in residential, commercial and hospitality applications. Fixture mounts to standard junction box (not included).

Construction

Stamped metal with perforations. Housing is die-formed steel. Standard mounting holes and hardware included. Power supply connections must be made inside junction box (not included).

Finish

Painted all White or Black with Gold inner finish.

Diffuser

White acrylic.

Electrical

D1 Driver

Input 120 VAC, 60 Hz. The LED driver is dimmable with a 2-wire (TRIAC) or electronic low voltage (ELV) dimmer switch.

D2 Driver

Input 120-277 VAC 60 Hz. LED driver is dimmable 0-10V DC.

LED

Integrated LED modules capable of producing:
17.5W = 1400 source lumens, 700 delivered lumens
31W = 2600 source lumens, 1433 delivered lumens
3000K (CCT). Rated for 50,000 Hrs. 90 CRI.

Certification

All fixtures are cETLus listed for indoor damp locations.

Warranty

Limited warranty: This fixture is free from defects in materials and workmanship for a period of 5 years from date-of-purchase.

**Specifications and dimensions
subject to change without notice.**

Ordering Information:

Black/Gold	White	LED	Source Lumens	Delivered Lumens	CCT	DIA.	D
ASHF1214L30D1BK	ASHF1214L30D1WH	17.5W	1400	700	3000K	12"	4"
ASHF1214L30D2BK	ASHF1214L30D2WH	17.5W	1400	700	3000K	12"	4"
ASHF1626L30D1BK	ASHF1626L30D1WH	31W	2600	1433	3000K	16"	4-1/2"
ASHF1626L30D2BK	ASHF1626L30D2WH	31W	2600	1433	3000K	16"	4-1/2"



Black/Gold



White

