



## Atlas Flush Mount ATLF Series

### Features

This low profile, clean appearance, surface mounted wrap provides a wide distribution of light. Products can be used in various applications including corridors, closets, bath, showers, hallway, kitchen and anywhere general lighting is needed. Fixture mounts to standard junction box (not included).

### Construction

Housing is die-formed of 22-gauge steel. Standard mounting holes are included. Power supply connections can be made inside the fixture wire way or in a junction box (not included).

### Finish

Satin nickel or oil-rubbed bronze frame finish.

### Diffuser

White diffuser is made of engineered LED acrylic material.

### Electrical

Input 120 VAC, 60 Hz. The driver is dimmable with a 2-wire (Triac) or electronic low voltage (ELV) dimmer switch.

### LED

Integrated LED modules capable of producing:  
15" - 18.5W, 1100 source lumens  
27" - 26W, 1800 source lumens  
3000K (CCT). Rated for 50,000 Hrs., 90 CRI.

### Certification

cETLus listed for damp locations.  
Title 24/JA8 Compliant  
ENERGY STAR® qualified  
Suitable for use in clothes closets when installed in accordance with the NEC 410.16 spacing requirements

### Warranty

Limited warranty: This fixture is free from defects in materials and workmanship for a period of 5 years from date-of-purchase.

**Specifications and dimensions subject to change without notice.**

## Ordering Information:

Satin Nickel		Oil-Rubbed Bronze		LED	Source Lumens	CCT	L	W	D
ATLF12121100L30D1SN		ATLF12121100L30D1RB		18.5W	1100	3000K	15"	15"	2"
ATLF12241800L30D1SN		ATLF12241800L30D1RB		26W	1800	3000K	27"	15"	2"

LOCATION		DATE
PREPARED BY		QUANTITY
COMMENTS		FIXTURE TYPE
CATALOG NUMBER		

