

# Boon LED Outdoor Sconce BONW Series

### **Features**

Decorative metal cut housing. Ideal use in hallways, entrances or anywhere general lighting is needed. Provides lighting in residential, commercial and hospitality applications. Meets ADA requirements. Fixture mounts to standard junction box (not included).

#### Construction

Back plate is die-formed of 22-gauge steel. Standard mounting holes and hardware are included. Power supply connections must be made inside a junction box (not included).

#### **Finish**

All metal parts are powder coated in White or Black.

#### Diffuser

Frosted glass diffuser.

#### Electrical

Input 120-277VAC / 60Hz. Compatible with 0-10V dimmers. Minimum starting temp -4° F/-20° C

#### **LED**

Fixture includes a LED modules capable of producing: 12W = 1000 source lumens, 589 delivered lumens 3000K (CCT). Rated for 50,000 Hrs., 90 CRI.


#### Certification

All fixtures are cETLus listed for wet locations. ADA

## Warranty

Limited warranty: This fixture is free from defects in materials and workmanship for a period of 5 years from date of purchase.

Specifications and dimensions subject to change without notice.


















# **Ordering Information:**

				Delivered				
White	Black	LED	Lumens	Lumens	CCT	H	W	D
BONW071710L30D2WH	BONW071710L30D2BK	12W	1000	589	3000K	16"	6"	3"