

Brio LED Sconce BRS Series

Features

Half-round wall mount with decorative metal bands and a white acrylic diffuser. Open top and bottom for wall wash effect. Ideal use in hallways, entrances or anywhere general lighting is needed. Provides lighting in residential, commercial and hospitality applications. Meets ADA requirements. Fixture mounts standard to junction box (not included).

Construction

Back plate is die-formed of 22-gauge steel. Decorative bands are .060" extruded aluminum with an apparent thickness of .100" that are screwed to a 22-gauge back plate. Standard mounting holes and hardware are included. Power supply connections must be made inside a junction box (not included).

Finish

Metal bands and backplate are finished in Satin Nickel or Oil-Rubbed Bronze.

Diffuser

Diffuser is .100" thick matte white extruded acrylic lens that installs from the top and slides into position. Allow 18" from top of fixture to any obstruction to clear lens installation.

Electrical

Input 120-277 VAC 60 Hz. 0.14A at 120 VAC. Compatible with residential (TRIAC/ELV) and commercial (0-10V) dimmers. TRIAC and ELV dimming only at 120 VAC.

LED

Integrated LED modules capable of producing: 17W, 1400 source lumens
Adjustable Choice 3000K, 3500K, 4000K (CCT).
Rated for 50,000 Hrs. 90 CRI.

Certification

All fixtures are cETLus listed for indoor damp locations. ADA

Warranty

Limited warranty: This fixture is free from defects in materials and workmanship for a period of 5 years from date-of-purchase.

Specifications and dimensions subject to change without notice.

Ordering Information:

			Source					
Satin Nickel	Oil-Rubbed Bronze	LED	Lumens	Adjustable CCT	H	W	D	MC
BRS071814LAJUDSN	BRS071814LAJUDRB	17W	1400	3000K/3500K/4000K	18"	7-1/4"	4"	9"

LOCATION	DATE
PREPARED BY	QUANTITY
COMMENTS	
	FIXTURE TYPE
CATALOG	
NUMBER	











Satin Nickel

Oil-Rubbed Bronze

