

Bowen LED Sconce BWNS Series

Features

Sleek contemporary styling with die-cast metal backplate and accent bar. Ideal use in hallways, entrances or anywhere general lighting is needed. Provides lighting in residential, commercial and hospitality applications. Meets ADA requirements. Fixture mounts to standard junction box (not included).

Construction

Back plate is die-formed of 22-gauge steel. Standard mounting holes and hardware are included. Power supply connections must be made inside a junction box (not included).

Finish

Satin Brass or Satin Nickel.

Diffuser

White acrylic diffuser.

Electrical

Input 120 VAC 60 Hz. Compatible with residential TRIAC and ELV dimmers.

LED

Integrated LED modules capable of producing: 15.5W = 1200 source lumens. 808 delivered lumens 3000K (CCT) rated for 50,000 hrs., 90 CRI


Certification

All fixtures are cETLus listed for indoor damp locations. ADA

Warranty

Limited warranty: This fixture is free from defects in materials and workmanship for a period of 5 years from date of purchase.


Specifications and dimensions subject to change without notice.











Ordering Information:

			Source	Delivered				
Satin Brass	Satin Nickel	LED	Lumens	Lumens	CCT	Н	W	D
RWNS051412L 30D1SB	BWNS051412L 30D1SN	15 5\\\/	1200	808	3000K	14-1/4"	4-1/2"	3-3/4"