



LOCATION		DATE
PREPARED BY		QUANTITY
COMMENTS		FIXTURE TYPE
CATALOG NUMBER		

Cirrus LED Flush Mount C2F Series

Features

A round floating cloud style with a white diffuser.
Ideal use in kitchens, hallways, and anywhere general lighting is needed.
Provides lighting in residential, commercial and hospitality applications.
Fixture mounts to standard junction box (not included).

Construction

A 22-gauge steel housing made by stamping process and painted in lighting grade white to provide long lasting finish with 3 side white screws to hold molded diffuser. Standard mounting holes and hardware included. Power supply connections must be made inside a junction box (not included).

Finish

White finish.

Diffuser

0.070" thick smooth white acrylic.

Electrical

Input 120VAC / 60 Hz.
Compatible with TRIAC and ELV dimmers.

LED

Integrated LED modules capable of producing:
17W = 1600 source lumens, 1258 delivered lumens
27W = 2400 source lumens, 1600 delivered lumens
35W = 3100 source lumens, 2236 delivered lumens
Adjustable Choice 3000K, 3500K, 4000K (CCT).
Rated for 50,000 Hrs. 90 CRI.

Certification

All fixtures are cETLus listed for indoor damp locations.
ENERGY STAR® qualified.
T24-JA8 Compliant.
Suitable for use in clothes closets when installed in accordance with the NEC 410.16 spacing requirements.

Options for 14" and 19" ONLY

Emergency Battery Back-Up (add -BB to the end of the model number)


Warranty

Limited warranty: This fixture is free from defects in materials and workmanship for a period of 5 years from date of purchase.

**Specifications and dimensions
subject to change without notice.**



FLUSH MOUNT



BATTERY BACKUP

Ordering Information:

White	LED	Source Lumens	Delivered Lumens	Adjustable CCT	DIA.	D
C2F111600LAJD1	17W	1600	1258	3000K/3500K/4000K	11"	3"
C2F142400LAJD1	27W	2400	1600	3000K/3500K/4000K	14"	3"
C2F193100LAJD1	35W	3100	2236	3000K/3500K/4000K	19"	3"