



Carlisle LED Semi-Flush Mount CAC Series

Features

Metal trim bands and canopy with a white floating diffuser. Ideal use in kitchens, hallways, and anywhere general lighting is needed. Provides lighting in residential, commercial and hospitality applications. Fixture mounts to standard junction box (not included).

Construction

A 22-gauge steel pan made by stamping process and painted in lighting grade white. A vacuum formed diffuser is secured with decorative dual metal bands. Standard mounting holes and hardware included. Power supply connections must be made inside a junction box (not included).

Finish

Satin nickel metal trim bands.

Diffuser

0.080" thick vacuum formed smooth white acrylic.

Electrical

Input 120 VAC / 60 Hz.

Compatible with TRIAC and ELV dimmers.

LED

Integrated LED modules capable of producing:

12W = 1200 source lumens, 967 delivered lumens

27W = 2400 source lumens, 1810 delivered lumens

35W = 3100 source lumens, 2947 delivered lumens

Adjustable Choice 3000K, 3500K, 4000K (CCT).

Rated for 50,000 Hrs., 90 CRI.

Certification

All fixtures are cETLus listed for indoor damp locations.

ENERGY STAR® qualified


T24/JA8 Compliant

Warranty

Limited warranty: This fixture is free from defects in materials and workmanship for a period of 5 years from date of purchase.

**Specifications and dimensions
subject to change without notice.**

LOCATION		DATE
PREPARED BY		QUANTITY
COMMENTS		FIXTURE TYPE
CATALOG NUMBER		



Ordering Information:

Satin Nickel	LED	Source Lumens	Delivered Lumens	Adjustable CCT	DIA.	D
CAC121200LAJD1	12W	1200	967	3000K/3500K/4000K	12"	8-3/4"
CAC142400LAJD1	27W	2400	1810	3000K/3500K/4000K	14"	9-1/4"
CAC243100LAJD1	35W	3100	2947	3000K/3500K/4000K	24"	10-1/4"