



LOCATION		DATE
PREPARED BY		QUANTITY
COMMENTS		FIXTURE TYPE
CATALOG NUMBER		

## Caden LED Pendant CADP Series

### Features

This pendant utilizes LED low voltage technology in various length acrylic cylinders. Cylinder is 2-1/2" in diameter and is available in several finishes. Light engine includes LED module rated at 50,000 hours. Pendant is suspended from 9' cord that can be cut to height and retained with a set screw and strain relief bushing. Product can be used over receptions desks, restaurants, and in any task lighting application. Driver is located in the canopy which mounts to standard junction box (not included).

### Construction

Acrylic cylinder is attached to the fixture via top and bottom endcaps. Canopy fits over a standard junction box. Power supply connections must be made inside a junction box (not included).

### Finish

Black or Satin Nickel.

### Diffuser

Cylinder is white acrylic.

### Electrical

Input 120-277 VAC 60 HZ.  
0-10V dimming (120-277V).  
TRIAC and ELV dimming (120V only).

### LED

Integrated LED modules capable of producing:  
25W = 2800 source lumens, 2036 delivered lumens  
29W = 3300 source lumens, 2665 delivered lumens  
34W = 3800 source lumens, 2946 delivered lumens  
3000K (CCT). Rated for 50,000 Hrs., 90 CRI.

### Certification

cETLus listed for indoor damp locations.

Specifications and dimensions  
subject to change without notice.

## Ordering Information:

Black	Satin Nickel	LED	Source Lumens	Delivered Lumens	CCT	DIA.	H
CADP24L30UDBK	CADP24L30UDSN	25W	2800	2036	3000K	2-1/2"	24"
CADP36L30UDBK	CADP36L30UDSN	29W	3300	2665	3000K	2-1/2"	36"
CADP48L30UDBK	CADP48L30UDSN	34W	3800	2946	3000K	2-1/2"	48"

