

LOCATION	DATE
PREPARED BY	QUANTITY
COMMENTS	FIXTURE TYPE
CATALOG NUMBER	

Caden Multi Linear Pendant CADP Series

Features

This pendant features a mix of 24", 36" and 48" luminous acrylic cylinders with 9 ft. adustable cords. Product can be used over reception desks, restaurants, and in public spaces. This fixture mounts to a standard junction box (not included).

Construction

The canopy fits over a standard junction box. Power supply connections must be made inside a junction box (not included).

Finish

Black or Satin Nickel.

Electrical

Input 120-277 VAC 60 HZ. 0-10V dimming (120-277V). TRIAC and ELV dimming (120V only).

Lamping

Integrated LED modules capable of producing: 176W = 19800 source lumens, 15294 delivered lumens 3000K (CCT). Rated for 50,000 Hrs., 90 CRI.

Certification


All fixtures are cETLus listed for indoor damp locations.

Warranty

Limited warranty: This fixture is free from defects in materials and workmanship for a period of 5 years from date of purchase.

Specifications and dimensions subject to change without notice.





Ordering Information:

			Source	Delivered				
Black	Satin Nickel	LED	Lumens	Lumens	ССТ	н	L	w
CADP99L30UDBKLNR6	CADP99L30UDSNLNR6	176W	19800	15294	3000K	48″	36″	5″