

Carlisle LED Flush Mount - 5 CCT CAF Series

Features

Metal trim bands with a white floating diffuser. Ideal use in kitchens, hallways, and anywhere general lighting is needed. Provides lighting in residential, commercial and hospitality applications. Fixture mounts to standard junction box (not included).

Construction

A 22-gauge steel pan made by stamping process and painted in lighting grade white. A vacuum formed diffuser is secured with decorative dual metal bands. Standard mounting holes and hardware included. Power supply connections must be made inside a junction box (not included).

Finish

Satin nickel metal trim bands.

Diffuser

0.080" thick vacuum formed smooth white acrylic.

Electrical

Input 120 VAC / 60 Hz.
Compatible with TRIAC and ELV dimmers.

LED

Integrated LED modules capable of producing: 12W = 967 delivered lumens 27W = 1810 delivered lumens Adjustable Choice 2700K, 3000K, 3500K, 4000K, 5000K (CCT). Rated for 50,000 Hrs., 90 CRI.

Certification

All fixtures are cETLus listed for indoor damp locations. ENERGY STAR® qualified
Title 24/JA8 Compliant
Suitable for use in clothes closets when installed in accordance with the NEC 410.16 spacing requirements.

Options for 14" ONLY

Emergency Battery Back-Up (add -BB to the end of the model number)

Warranty

Limited warranty: This fixture is free from defects in materials and workmanship for a period of 5 years from date of purchase.

Specifications and dimensions subject to change without notice.

Ordering Information:

		Delivered			
Satin Nickel	LED	Lumens	Adjustable CCT	DIA.	D
CAF121200L5AJD1	12W	967	2700K/3000K/3500K/4000K/5000K	12"	3-1/2"
CAF142400L5A.JD1	27W	1810	2700K/3000K/3500K/4000K/5000K	14"	4"

LOCATION	DATE
PREPARED	
BY	QUANTITY
J	
COMMENTS	
	FIXTURE TYPE
CATALOG NUMBER	















