

Capri LED Flush Mount CFF Series

Features

Metal trim band with a white acrylic diffuser. Ideal use in kitchens, hallways, and anywhere general lighting is needed. Provides lighting in residential, commercial and hospitality applications. Fixture mounts to standard junction box (not included).

Construction

A 22-gauge steel housing made by spinning process and painted. 3 spring clips support slip on diffuser. Standard mounting holes and hardware included. Power supply connections must be made inside a junction box (not included).

Finish

White or Brushed Nickel metal trim band.

Diffuser

0.050" thick white acrylic.

Electrical

Input 120 VAC / 60 Hz.
Compatible with TRIAC and ELV dimmers.

LED

Integrated LED modules capable of producing: 17W = 1600 source lumens, 1100 delivered lumens 27W = 2400 source lumens, 1755 delivered lumens 35W = 3100 source lumen, 2275 delivered lumenss Adjustable Choice 3000K, 3500K, 4000K (CCT). Rated for 50,000 Hrs., 90 CRI.

Certification

All fixtures are cETLus listed for indoor damp locations.
ENERGY STAR® qualified
Title 24/JA8 Compliant
Suitable for use in clothes closets when installed in accordance with the NEC 41016 spacing requirements.

Options for 14" and 19" ONLY

Emergency Battery Back-Up (add -BB to the end of the model number)

Warranty

Limited warranty: This fixture is free from defects in materials and workmanship for a period of 5 years from date-of-purchase.

Specifications and dimensions subject to change without notice.

LOCATION	DATE
PREPARED BY	QUANTITY
COMMENTS	FIXTURE TYPE
CATALOG NUMBER	




















Ordering Information:

White	Brushed Nickel	LED	Source Lumens	Delivered Lumens	Adjustable CCT	DIA.	D
CFF111600LAJD1WH	CFF111600LAJD1BN	17W	1600	1100	3000K/3500K/4000K	11"	3"
CFF142400LAJD1WH	CFF142400LAJD1BN	27W	2400	1755	3000K/3500K/4000K	14"	3-7/16"
CFF193100LAJD1WH	CFF193100LAJD1BN	35W	3100	2275	3000K/3500K/4000K	19"	4-3/16"