

Camden LED Flush Mount CMF Series

Features

Shallow mushroom style with a white acrylic diffuser. Ideal use in kitchens, hallways, and anywhere general lighting is needed. Provides lighting in residential, commercial and hospitality applications. Fixture mounts to standard junction box (not included).

Construction

A 22-gauge steel housing made by stamping process and painted in lighting grade white. 3 side white screws to hold molded diffuser. Standard mounting holes and hardware included. Power supply connections must be made inside a junction box (not included).

Finish

White

Diffuser

0.070" thick smooth white acrylic.

Electrical

Input 120 VAC / 60 Hz. Compatible with TRIAC and ELV dimmers.

Lamping

Integrated LED modules capable of producing: 17W = 1600 source lumens, 1000 delivered lumens 27W = 2400 source lumens, 1514 delivered lumens 35W = 3100 source lumens, 1950 delivered lumens Adjustable Choice 3000K, 3500K, 4000K (CCT). Rated for 50,000 Hrs., 90 CRI.

Certification

All fixtures are cETLus listed for indoor damp locations. ENERGY STAR® qualified Title 24/JA8 Compliant Suitable for use in clothes closets when installed in accordance with the NEC 410.16 spacing requirements.

Options for 14" and 19" ONLY

Emergency Battery Back-Up (add -BB to the end of the model number)

Warranty

Limited warranty: This fixture is free from defects in materials and workmanship for a period of 5 years from date-of-purchase.

Specifications and dimensions subject to change without notice.









FLUSH MOUNT



BATTERY BACKUP

Ordering Information:

White	LED		Delivered Lumens	Adjustable CCT	DIA.	D
CMF111600LAJD1	17W	1600	1000	3000K/3500K/4000K	11″	3-3/4″
CMF142400LAJD1	27W	2400	1514	3000K/3500K/4000K	14″	3-3/4"
CMF193100LAJD1	35W	3100	1950	3000K/3500K/4000K	19″	3-3/4"