

Commons LED Sconce CMNS Series

Features

Faceted metal housing with dynamic metal faceplate. Ideal use in hallways, entrances or anywhere general lighting is needed. Provides lighting in residential, commercial and hospitality applications. Vertical or horizontal mounting.

Meets ADA requirements. Fixture mounts to standard junction box (not included).

Construction

Back plate is die-formed of 22-gauge steel. Standard mounting holes and hardware are included. Power supply connections must be made inside a junction box (not included).

Finish

White powder coat.

Diffuser

Faceted metal faceplate.

Electrical

Input 120-277 VAC, 60 Hz LED. LED driver is 0-10V DC dimmable.

I FD

Integrated LED modules capable of producing: 13W = 800 source lumens, 266 delivered lumens 24W = 1600 source lumens, 612 delivered lumens 3000K (CCT) rated for 50,000 hrs., 90 CRI.


Certification

All fixtures are cETLus listed for indoor damp locations. ADA

Warranty

Limited warranty. This fixture is free from defects in materials and workmanship for a period of 5 years from date of purchase.

Specifications and dimensions subject to change without notice.


















Ordering Information:

			Delivered				
White	LED	Lumens	Lumens	CCT	Н	W	D
CMNS070708L30D2WH	13W	800	266	3000K	7"	7"	2"
CMNS072716L30D2WH	24W	1600	612	3000K	27"	7"	2"