

Coronado Narrow LED Striplight CRDL Series

Features

This clean appearance, surface mounted cloud provides a wide distribution of light with a white diffuser. It can be used in various applications including offices, corridors, garages, kitchens and public spaces. Fixture mounts to standard junction box (not included) on a ceiling.

Construction

Housing is die-formed of 22-gauge steel. Power supply connections can be made inside the fixture wire way or inside a junction box (not included).

Finish

Housing is finished in lighting grade white baked gloss enamel paint.

Diffuser

White acrylic diffuser.

Electrical

Input 120-277VAC / 60Hz. Not compatible with dimmers.

LED

Integrated LED modules capable of producing: 17W =1900 source lumens 22W = 2400 source lumens 43W = 4700 source lumens 4000K (CCT). Rated for 50,000 hours, 80 CRI.

Certification

cETLus listed for indoor damp locations.


Warranty

Limited warranty: This fixture is free from defects in materials and workmanship for a period of 5 years from date-of-purchase.

Specifications and dimensions subject to change without notice.

LOCATION	DATE
PREPARED BY	QUANTITY
COMMENTS	FIXTURE TYPE
CATALOG NUMBER	





Ordering Information:

Source									
Cool White	LED	Lumens	CCT	L	W	Н			
CRDL022419L40MVWH	17W	1900	4000K	24"	2-1/2"	2-1/2"			
CRDL024624L40MVWH	22W	2400	4000K	46-1/2"	2-1/2"	2-1/2"			
CDDI 024647L40M\/\\/U	17/1/	4700	1000K	16-1/2"	2-1/2"	2-1/2"			