



LOCATION		DATE
PREPARED BY		QUANTITY
COMMENTS		FIXTURE TYPE
CATALOG NUMBER		

Dayton LED Pendant DYP Series

Features

Transitional shaded pendant with satin nickel accent detail. Pendant has a satin nickel finish and includes a hard backed whitelinen shade with white acrylic bottom diffuser; open top and center lock up. Suspended with a 3 ft. adjustable rigid stem expandable up to 9 ft. Product can be used over receptions desks, restaurants, and in public spaces. Canopy mounts to a standard junction box (not included).

Construction

Gear plate is die-formed of 20-gauge steel. Trim ring is 22-gauge steel and finial is die cast aluminum. Power supply connections must be made inside a junction box (not included).

Finish

Pan is finished in lighting grade white baked gloss enamel paint. Trim ring and finial have an applied satin nickel finish with a clear lacquer topcoat.

Electrical

Input 120-277 VAC 60 HZ.
Compatible with residential (TRIAC/ELV) and commercial (0-10V) dimmers. TRIAC and ELV dimming only at 120 VAC.

LED

Integrated LED modules capable of producing:
24" - 35W = 3200 source lumens
30" - 46W = 4400 source lumens
Adjustable Choice 3000K, 3500K, 4000K (CCT).
Rated for 50,000 Hrs., 90 CRI.

Certification

All fixtures are cETLus listed for indoor damp locations.

Options

Additional stems sold separately.

Warranty

Limited warranty: This fixture is free from defects in materials and workmanship for a period of 5 year from date of purchase.

Specifications and dimensions
subject to change without notice.

Ordering Information:

Satin Nickel	LED	Source Lumens	Adjustable CCT	DIA.	H
DYP2432LAJUDSN	35W	3200	3000K/3500K/4000K	24"	9"
DYP3044LAJUDSN	46W	4400	3000K/3500K/4000K	30"	12"

