

Holly LED Overbed HLYB Series

Features

A white acrylic diffuser with decorative metal trim provides a soft glow accent to this contemporary wall mount senior care overbed light. The Holly includes an on/off pull switch, standard (120 volt only).

Construction

The light wiring channel is formed from 22-gauge steel and is provided with keyhole mounting slots and wiring access. Fixture can mount horizontally only. Power connections can be made in the fixture wiring channel or in a standard junction box (not included).

Finish

Satin nickel. Internal housing is finished in white.

Diffuser

White acrylic. Frame mounts to electrical channel with two decorative screws.

Electrical

Input 120VAC / 60Hz. Provides 50 footcandles of reading light over bed. On/off control pull-switch is included. Not compatible with dimmers.

LED

Integrated LED modules capable of producing: 36" - 50W = 5000 source lumens, 3910 delivered lumens 48" - 65W = 6500 source lumens, 5000 delivered lumens 3000K (CCT). Rated for 50,000 Hrs., 80 CRI.

Certification

cETLus listed for damp locations. ADA

Warranty

Limited warranty: This fixture is free from defects in materials and workmanship for a period of 5 years from date-of-purchase.

Specifications and dimensions

subject to change without notice.

Ordering Information:

		Source	Delivered				
Satin Nickel	LED	Lumens	Lumens	ССТ	L	н	D
HLYB36L30ENSN	50W	5000	3910	3000K	36″	6″	3″
HLYB48L30ENSN	65W	6500	5000	3000K	48″	6″	3″

LOCATION	DATE
PREPARED BY	QUANTITY
COMMENTS	FIXTURE TYPE
CATALOG NUMBER	





