



LOCATION		DATE
PREPARED BY		QUANTITY
COMMENTS		FIXTURE TYPE
CATALOG NUMBER		

## Hermosa LED Pendant HRP Series

### Features

Clear or tinted outer glass pendant is suspended with a 9 foot adjustable cord. Canopy mounts to a standard junction box (not included).

### Construction

The glass cylinder is 16" tall and 6" in diameter and held together into place by stem and top cap. The canopy fits over a standard junction box. Power supply connections must be made inside a junction box (not included).

### Finish

The canopy is plated in Satin Nickel.

### Diffuser

Glass cylinder pendant is .40" thick. Glass colors include aqua (AQ), clear (CL), clear swirl (CS), and brown (BR).

### Electrical

#### D1 Driver

Direct wired with a constant current low voltage electronic LED driver rated at 120 VAC. The driver is dimmable with a 2-wire (Triac) or electronic low voltage (ELV) dimmer switch.

#### D2 Driver

Direct wired with a constant current low voltage electronic LED driver rated for 120-277 VAC. LED driver is dimmable 0-10V DC.

### LED

All pendants include a 10W LED module. Light engine produces 1000 source lumens. 3000K or 4000K (CCT). 50,000 hr. LED life, 90 CRI.

### Certification

All fixtures are ETL listed for indoor damp locations.

### Specifications and dimensions

subject to change without notice.



Brown

Clear



Clear Swirl

Aqua

## Ordering Information:

6" DIA. x 16-3/4" H

Series	Source Lumens	LED	CCT	Driver	Finish	Glass
HRP	1000	L	30 3000K 40 4000K	D1 Voltage (120V TRIAC Dimming) D2 Voltage (120-277V 0-10V Dimming)	SN Satin Nickel	AQ Aqua CL Clear CS Clear Swirl BR Brown

Example: HRP1000L30D1SNCS

