



LOCATION		DATE
PREPARED BY		QUANTITY
COMMENTS		FIXTURE TYPE
CATALOG NUMBER		

Ideal LED Sconce IDS Series

Features

Simple modern curved white glass with metal ends. Ideal use in hallways, entrances or anywhere general lighting is needed. Provides lighting in residential, commercial and hospitality applications. Meets ADA requirements. Fixture mounts standard to junction box (not included).

Construction

Back plate is die-formed of 22-gauge steel. Standard mounting holes and hardware are included. Power supply connections must be made inside a junction box (not included).

Finish

Back plate is finished in lighting grade white baked gloss enamel paint. Trim band is die-cast aluminum with a plated Satin Nickel.

Diffuser

Blow formed matte white glass.

Electrical

Input 120-277 VAC, 60 Hz LED.
Not compatible with dimmers.

LED

Integrated LED modules capable of producing:
15W = 1300 source lumens, 520 delivered lumens
4000K (CCT) rated for 50,000 hrs., 80 CRI.

Certification

All fixtures are cETLus listed for indoor damp locations.
ADA

Warranty

Limited warranty: This fixture is free from defects in materials and workmanship for a period of 5 years from date of purchase.

Specifications and dimensions
subject to change without notice.

Ordering Information:

Satin Nickel	LED	Source Lumens	CCT	H	W	D
IDS09101600L41SN	15W	1300	4000K	10"	8-3/4"	3-1/2"

