

Dorset LED Sconce IDSS Series

Features

Decorative metal accents with matte white glass. Open top and enclosed white acrylic bottom. Ideal use in hallways, entrances or anywhere general lighting is needed. Provides lighting in residential, commercial and hospitality applications. Meets ADA requirements. Fixture mounts to standard junction box (not included).

Construction

Back plate is die-formed of 22-gauge steel. Standard mounting holes and hardware are included. Power supply connections must be made inside a junction box (not included).

Finish

Backplate and accents finished in Satin Nickel.

Diffuser

Curved formed matte white glass.

Electrical

Input 120-277V VAC/ 60 Hz. Not compatible with dimmers.

LED

Integrated LED modules capable of producing: 14W = 1300 source lumens 4000K (CCT) rated for 50,000 hrs., 80 CRI.

Certification

All fixtures are cETLus listed for indoor damp locations. ADA

Warranty

Limited warranty: This fixture is free from defects in materials and workmanship for a period of 5 years from date-of-purchase.

Specifications and dimensions subject to change without notice.

Ordering Information:

	Source						
Satin Nickel	LED	Lumens	ССТ	Н	W	D	
IDSS09111600L41SN	14W	1300	4000K	11-5/8"	9″	4″	

LOCATION	DATE
PREPARED BY	QUANTITY
COMMENTS	FIXTURE TYPE
CATALOG NUMBER	





