



## Lambert LED Flush Mount LBTF Series

### Features

Ornamental metal accents with a grey linen fabric side diffuser. White bottom acrylic diffuser. Ideal use in kitchens, hallways, and anywhere general lighting is needed. Provides lighting in residential, commercial and hospitality applications. Fixture mounts to standard junction box (not included).

### Construction

The canopy is made of 22-gauge cold rolled steel. The LED pan is white painted. Standard mounting holes and hardware included. The canopy fits over a standard junction box. Power supply connections must be made inside a junction box (not included).

### Finish

Satin nickel metal accents.

### Diffuser

Grey linen fabric side diffuser.  
White acrylic bottom diffuser.

### Electrical

Input 120-277 VAC 60 HZ.  
Compatible with residential (TRIAC/ELV) and commercial (0-10V) dimmers.  
TRIAC and ELV dimming only at 120 VAC.

### LED

Integrated LED modules capable of producing:  
30W = 2400 source lumens, 1675 delivered lumens  
42W = 3200 source lumens, 2520 delivered lumens  
Adjustable Choice 3000K, 3500K, 4000K (CCT).  
Rated for 50,000 Hrs., 90 CRI.

### Options

Emergency Battery Back-Up (add -BB to the end of the model number)  
Motion Sensor (add -MS to the end of the model number)  
Emergency Battery Back-Up with Motion Sensor (add -MSBB to the end of the model number)

### Certification

All fixtures are cETLus listed for indoor damp locations.

### Warranty

Limited warranty: This fixture is free from defects in materials and workmanship for a period of 5 years from date of purchase.

### Specifications and dimensions

subject to change without notice.

### Ordering Information:

Satin Nickel/Grey	LED	Source Lumens	Delivered Lumens	Adjustable CCT	DIA.	D
LBTF1624LAJUDSNGY	30W	2400	1675	3000K/3500K/4000K	16"	4"
LBTF2032LAJUDSNGY	42W	3200	2520	3000K/3500K/4000K	20"	4"

LOCATION		DATE
PREPARED BY		QUANTITY
COMMENTS		FIXTURE TYPE
CATALOG NUMBER		



BATTERY BACKUP



FLUSH MOUNT