

Miller LED Vanity MLRV Series

Features

Decorative vanity with a white acrylic diffuser and satin nickel accents. Ideal use for general lighting in indoor residential, commercial, and hospitality applications. Fixture can be mounted to a standard junction box (not included).

Construction

Fabricated metal housing. Power supply connections must be made inside a junction box (not included).

Finish

Satin Nickel backplate and accents finish.

Diffuser

White acrylic diffuser.

Electrical

Input 120 VAC 60 HZ. Compatible with residential TRIAC and ELV dimmers.

I FD

Integrated LED modules capable of producing: 17W = 1700 source lumens, 1580 delivered lumens 25W= 2500 source lumens, 2168 delivered lumens Adjustable Choice 3000K, 3500K, 4000K (CCT). Rated for 50,000 Hrs., 90 CRI.

Certification

All fixtures are cETLus listed for indoor damp locations.

Warranty

Limited warranty: This fixture is free from defects in materials and workmanship for a period of 5 year from date of purchase.


Specifications and dimensions subject to change without notice.











Ordering Information:

		Source	Delivered					
Satin Nickel	LED	Lumens	Lumens	Adjustable CCT	L	Н	D	
MLRV2605LAJD1SN	17W	1700	1580	3000K/3500K/4000K	24-3/8"	4-1/2"	4-1/4"	
MLRV3805LAJD1SN	25W	2500	2168	3000K/3500K/4000K	35-3/4"	4-1/2"	4-1/4"	