

Marquette LED Overbed MQTB Series

Features

White linen patterned acrylic front panel provides a soft glow accent to this contemporary wall mount senior care overbed light. The walnut trim accents identify the graceful shape. The Marquette provides both ambient and task light with a four way pull switch, standard (120 volt only). Top diffuser and bottom diffuser are frosted white acrylic.

Construction

The light wiring channel is formed from 22-gauge steel and is provided with keyhole mounting slots and wiring access. An internal divider provides separate lamp compartments for controlled up light and down light. The decorative bands are stamped steel and glued to the diffuser. Fixture can mount horizontally only. Power connections can be made in the fixture wiring channel or in a standard junction box (not included).

Finish

Metal ends have Walnut finish. Internal housing is finished in a lighting grade baked white enamel.

Diffuser

Diffuser is 0.070" thick matte white acrylic for the down light and a white linen pattern acrylic front. Frame mounts to electrical channel with two decorative screws.

Electrical

Input 120VAC / 60 Hz

Not compatible with dimmers. Integrated four position pull switch (on up, on down, on both, all off) and single pull switch for nightlight.

LED

Integrated LED modules capable of producing: 60W = 4050 source lumens 80W = 5400 source lumens Rated for 50,000 hours, 3000K (CCT), 90 CRI. Provides 50 footcandles of reading light over bed.

Certification

All fixtures are cETLus listed for indoor damp locations. ADA

Warranty

Limited warranty: This fixture is free from defects in materials and workmanship for a period of 5 years from date-of-purchase.

Specifications and dimensions subject to change without notice.

Ordering Information:

Walnut	LED	Source Lumens	CCT	L	н	D
MQTB3840L30ENWN	60W	1350 up/2700 down	3000K	38″	5″	4"
MQTB5054L30ENWN	80W	1800 up/3600 down	3000K	50″	5"	4"

LOCATION	DATE
PREPARED BY	QUANTITY
COMMENTS	FIXTURE TYPE
CATALOG NUMBER	





