

Novara LED NVS Series

Features

Diamond point formed metal. Ideal use in hallways, entrances or anywhere general lighting is needed. Provides lighting in residential, commercial and hospitality applications. Vertical or horizontal mounting. Meets ADA requirements. Fixture mounts to standard junction box (not included).

Construction

Back pan and mounting plate are die-formed steel. Standard mounting holes and hardware included, power supply connection must be made inside junction box (not included).

Finish

Plated satin nickel or satin brass* with clear top coat.

Diffuser

White acrylic.

Electrical

Input 120 VAC / 60 Hz. Compatible with residential TRIAC and ELV dimming.

LED

Fixture includes an LED module capable of producing: 15.5W = 1200 source lumens, 376 delivered lumens 3000K (CCT). Rated for 50,000 Hrs., 90 CRI.

Certification

All fixtures are cETLus listed for indoor damp locations. ADA

Warranty

Limited warranty: This fixture is free from defects in materials and workmanship for a period of 5 years from date of purchase.

Specifications and dimensions subject to change without notice.














Ordering Information:

			Source	Delivered				
Satin Nickel	Satin Brass*	LED	Lumens	Lumens	CCT	H	W	D
NVS5131200L30D1SN	NVS5131200L30D1SB	15.5W	1200	376	3000K	13"	4-1/2"	3-5/8"

*Special Order - consult factory for MOQ and lead time.