



LOCATION		DATE
PREPARED BY		QUANTITY
COMMENTS		FIXTURE TYPE
CATALOG NUMBER		

Pearson LED Flush Mount PEAF Series

Features

Contemporary flush mount features a simple and clean design with metal accents. White acrylic diffuser. Ideal use in kitchens, hallways, and anywhere general lighting is needed. Provides lighting in residential, commercial and hospitality applications. Fixture mounts to standard junction box (not included).

Construction

Back plate is die-formed of 22-gauge steel. Standard mounting holes and hardware are included. Power supply connections must be made inside a junction box (not included).

Finish

All metal parts are painted satin nickel or white.

Diffuser

.100" thick white fabricated acrylic diffuser.

Electrical

Input 120-277 VAC 60 HZ.
Compatible with residential (TRIAC/ELV) and commercial (0-10V) dimmers. TRIAC and ELV dimming only at 120 VAC.

LED

Integrated LED modules capable of producing:
15W = 1400 source lumens
30W = 2400 source lumens
Adjustable choice 2700K, 3000K, or 3500K (CCT).
Rated for 50,000 Hrs. 90 CRI.

Certification

All fixtures are cETLus listed for indoor damp locations.
*Title 24 Compliant with 12" fixture.

Warranty

Limited warranty: This fixture is free from defects in materials and workmanship for a period of 5 years from date-of-purchase.


**Specifications and dimensions
subject to change without notice.**



Satin Nickel



White



Ordering Information:

White	Satin Nickel	LED	Source Lumens	Adjustable CCT	L	W	D
PEAF1215LAJUDWH*	PEAF1215LAJUDSN*	15W	1400	2700K/3000K/3500K	12"	12"	3-3/16"
PEAF1624LAJUDWH	PEAF1624LAJUDSN	30W	2400	2700K/3000K/3500K	16"	16"	3-3/16"