

# Pasadena LED Outdoor Sconce PSDW Series

### **Features**

This LED light is ideal for security and general lighting.
3 in 1 color temperature adjustable option.
Decorative metal accents. Provides lighting in residential, commercial, and hospitality applications. Meets ADA requirements. Fixture mounts to standard junction box (not included).

### Construction

Standard mounting holes and hardware are included. Power supply connections must be made inside a junction box (not included).

### **Finish**

Textured grey or textured bronze powder coated finish.

### Diffusei

Diffuser is .100" thick matte white acrylic.

### **Electrical**

This unit is direct wired with a low voltage electronic LED driver. The constant current LED driver is rated for 120-277 VAC input, 0-10V dimmable. Minimum starting temp -20°F.

## Lamping

Fixture includes LED modules capable of producing: 12" - 20W, 2300 source lumens 18" - 28W, 3300 source lumens 3000K, 3500K, 4000K Adjustable (CCT). Rated for 50,000 Hrs. 90 CRI.

### Certification

All fixtures are cETLus listed for wet locations. ADA\*


### Warrantv

Limited warranty: This fixture is free from defects in materials and workmanship for a period of 5 years from date of purchase.

Specifications and dimensions subject to change without notice.

# LOCATION PREPARED BY COMMENTS CATALOG NUMBER DATE QUANTITY FIXTURE TYPE





# **Ordering Information:**

		Source				
Textured Grey	LED	Lumens	CCT	Н	W	D
PSDW071223LAJD2TG	20W	2300	3000K/3500K/4000K	12"	6"	3-3/4"
PSDW071833LAJD2TG	28W	3300	3000K/3500K/4000K	18"	6-3/4"	4"
Textured Bronze						
PSDW071223LAJD2BZ	20W	2300	3000K/3500K/4000K	12"	6"	3-3/4"
PSDW071833LAJD2BZ	28W	3300	3000K/3500K/4000K	18"	6-3/4"	4"