

# Rowan LED Sconce RWNS Series

#### **Features**

Modern wall sconce. Can be used in hallways, entrances, restrooms and anywhere general lighting is needed. Provides lighting in residential, commercial, and hospitality applications. Meets ADA requirements. Fixture can be mounted horizontally or vertically to a standard junction box (not included).

#### Construction

Back pan is die formed from 22-gauge steel. Metal construction with sealed white diffuser. Standard mounting holes and hardware are included. Power supply connections must be made inside a junction box (not included).

#### **Finish**

Metal housing is available in Satin Nickel or White powder coated finish.

#### Diffuser

Edge-lit diffuser is made of 0.10" thick standard white acrylic.

#### **Electrical**

Input 120-277VAC / 60 Hz. Compatible with 0-10V dimmers.

#### **LED**

Integrated LED modules capable of producing: 18" - 16W = 1400 source lumens, 472 delivered lumens 30" - 28W = 2400 source lumens, 568 delivered lumens 3000K (CCT). Rated for 50,000 hrs., 90 CRI


#### Certification

All fixtures are cETLus certified for indoor damp locations. ADA

### Warranty

Limited warranty: This fixture is free from defects in materials and workmanship for a period of 5 years from date-of-purchase.


Specifications and dimensions subject to change without notice.











MC - Mounting Center

## Ordering Information:

			Source	Delivered					
Satin Nickel	White	LED	Lumens	Lumens	CCT	Н	W	D	MC
RWNS180414L30D2SN	RWNS180414L30D2WH	16W	1400	472	3000K	18"	4"	2-1/2"	9"
RWNS300424L30D2SN	RWNS300424L30D2WH	28W	2400	568	3000K	30"	4"	2-1/2"	15"