

Ryland LED Vanity RYDV Series

Features

Contemporary vanity in satin nickel finish. Provides lighting in residential, commerical or hospitality applications. Fixture can be mounted horizontally or vertically to a standard junction box (not included) on a wall.

Construction

The wiring channel is formed from 22-gauge steel and is provided with standard mounting holes and wiring access. Power supply connections must be made inside a junction box (not included).

Finish

Plated in satin nickel finish.

Diffuser White acrylic diffus

White acrylic diffuser.

Electrical

Input 120-277VAC / 60Hz. Compatible with 0-10V dimmers.

LED

Intergrated LED modules capable of producing: 28 = 26W, 2200 source lumens, 1348 delivered lumens 38" = 37W, 3600 source lumens, 1907 delivered lumens 3000K (CCT). Rated for 50,000 Hrs., 90 CRI.

Certification

All fixtures are cETLus listed for indoor damp locations. ADA

Warranty

Limited warranty: This fixture is free from defects in materials and workmanship for a period of 5 years from date-of-purchase.

Specifications and dimensions subject to change without notice.



Ordering Information:

			Delivered				
Satin Nickel	LED	Lumens	Lumens	ССТ	L	н	D
RYDV280422L30D2SN			1348	3000K	28″	4"	3-1/2"
RYDV380436L30D2SN	38W	3600	1907	3000K	38″	4″	3-1/2"





