

Sheridan LED Sconce SHS Series

3in1 CCT



DATE

QUANTITY

FIXTURE TYPE



Features

Transitional style arm fixture with a top and bottom diffuser. Ideal use in hallways, entrances or anywhere general lighting is needed. Provides lighting in residential, commercial and hospitality applications. Meets ADA requirements. Fixture mounts standard to junction box (not included).

Construction

Back plate is die formed of 20-gauge steel. Standard mounting holes and hardware are included. The arms are tapered cast aluminum and require assembly to the backplate and wall. Power supply connections can be made inside a junction box (not included).

Finish

Backplate is finished in lighting grade white baked gloss enamel paint. Cast arm is finished in anodized Champagne or a plated Satin Nickel.

Diffuser

Diffuser is a hard backed cream linen shade (LN) white linen acrylic (LA). Shade mounts to back plate with two screws. Top and bottom diffusers are .100" matte white acrylic.

Electrical

Input 120-277 VAC 60 HZ.

Compatible with residential (TRIAC/ELV) and commercial (0-10V) dimmers. TRIAC and ELV dimming only at 120 VAC.

LED

Fixture includes LED modules capable of producing: Single Arm - 9W = 700 source lumens Double Arm - 17W = 1400 source lumens Adjustable Choice 3000K, 3500K, 4000K (CCT). Rated for 50,000 Hrs. 90 CRI.


Certification


All fixtures are cETLus listed for indoor damp locations. ADA

Warranty

Limited warranty: This fixture is free from defects in materials and workmanship for a period of 5 years from date of purchase.

Specifications and dimensions subject to change without notice.






LOCATION PREPARED

COMMENTS

CATALOG NUMBER

BY



MC - Mounting Center

Single Arm			Source				
Satin Nickel	Champagne	LED	Lumens	Adjustable CCT	H	W	D
CLICACIOAZI A ILIDANI A	CLICOCIONTE A ILIDACENE	014/	700	7000K/7E00K/4000K	10 1/2//	C 1/0"	7 1/0"

Double Arm							
Satin Nickel	Champagne	LED	Lumens	Adjustable CCT	Н	W	D
SHS121814LAJUDSNLA	SHS121814LAJUDACLN	17W	1400	3000K/3500K/4000K	18-1/2"	12-5/8"	3-1/2"