

Sinclair LED Flush Mount SNF Series

Features

Contemporary flush mount features a simple and clean design with metal accents. White acrylic diffuser. Ideal use in kitchens, hallways, and anywhere general lighting is needed. Provides lighting in residential, commercial and hospitality applications. Fixture mounts to standard junction box (not included).

Construction

Back plate is die-formed of 22-gauge steel. Standard mounting holes and hardware are included. Power supply connections must be made inside a junction box (not included).

Finish

All metal parts are plated satin nickel.

Diffuser

.100" thick white fabricated acrylic diffuser.

Electrical

Input 120-277 VAC 60 HZ.

Compatible with residential (TRIAC/ELV) and commercial (0-10V) dimmers. TRIAC and ELV dimming only at 120 VAC.

LED

Fixture includes a LED modules capable of producing: 15W = 1400 source lumens, 650 delivered lumens 30W = 2400 source lumens, 1700 delivered lumens Adjustable choice 2700K, 3000K, or 3500K (CCT). Rated for 50,000 Hrs. 90 CRI.

Certification

All fixtures are cETLus listed for indoor damp locations. *Title 24/JA8 Compliant with 14" fixture.

Warranty

Limited warranty: This fixture is free from defects in materials and workmanship for a period of 5 years from date-of-purchase.

Specifications and dimensions subject to change without notice.

Ordering Information:

		Source	Delivered				
Satin Nickel	LED	Lumens	Lumens	Adjustable CCT	L	W	D
SNF141400LAJUDSN*	15W	1400	650	2700K/3000K/3500K	14-1/4"	14-1/4″	3-5/8″
SNF172400LAJUDSN	30W	2400	1700	2700K/3000K/3500K	17-5/8″	17-5/8″	3-5/8"

LOCATION	DATE
PREPARED BY	QUANTITY
COMMENTS	FIXTURE TYPE
CATALOG NUMBER	





