



| | | |
|----------------|--|--------------|
| LOCATION | | DATE |
| PREPARED BY | | QUANTITY |
| COMMENTS | | FIXTURE TYPE |
| CATALOG NUMBER | | |

Spun LED Pendant SPP Series

Features

Hand-blown glass with white pattern molten glass cane. Pendant is suspended with a 9 foot adjustable cord. Canopy mounts to a standard junction box (not included).

Construction

The glass cylinder is 16-3/4" tall and 5" in diameter and held together into place by three decorative studs. The canopy fits over a standard junction box. Power supply connections must be made inside a junction box (not included).

Finish

The canopy is plated in Satin Nickel.

Diffuser

Glass cylinder pendant is .40" thick. Glass colors include clear (CL), smoke (SM) and steel blue (SB).

Electrical

D1 Driver

Direct wired with a constant current low voltage electronic LED driver rated at 120 VAC. The driver is dimmable with a 2-wire (Triac) or electronic low voltage (ELV) dimmer switch.

D2 Driver

Direct wired with a constant current low voltage electronic LED driver rated for 120-277 VAC. LED driver is dimmable 0-10V DC.

LED

All pendants include a 10W LED module. Light engine produces 1000 source lumens. 3000K or 4000K (CCT). 50,000 hr. LED life, 90 CRI.

Certification

All fixtures are ETL listed for indoor damp locations.

Specifications and dimensions

subject to change without notice.

Ordering Information:

5" DIA. x 16-3/4" H

| Series | Source Lumens | LED | CCT | Driver | Finish | Glass |
|--------|---------------|-----|----------------------|--|-----------------|---------------------------------------|
| SPP | 1000 | L | 30 3000K 40 4000K | D1 Voltage (120V TRIAC Dimming) D2 Voltage (120-277V 0-10V Dimming) | SN Satin Nickel | CL Clear SM Smoke SB Steel Blue |

Example: SPP1000L30D2SNSM



Clear

Smoke

Steel Blue

