

Summit LED Sconce SUMS Series

Features

Dramatic angular design. Indirect light with wall wash effect.
Ideal use in hallways, entrances or anywhere general lighting is needed.
Provides lighting in residential, commercial and hospitality applications.
Meets ADA requirements. Fixture mounts to standard junction box (not included).

Construction

Back plate is die-formed of 22-gauge steel. Standard mounting holes and hardware are included. Power supply connections must be made inside a junction box (not included).

Finish

All metal parts are painted in Black/Copper or White/Silver

Diffuser

None

Electrical

D1 - Input 120 VAC / 60Hz.
MV - Input 120-277 VAC/ 60 Hz.
Compatible with residential TRIAC and ELV dimmers (D1 ONLY).

LED

Integrated LED modules capable of producing: 20W = 1300 source lumens 3000K (CCT) rated for 50,000 hrs., 90 CRI.

Certification

All fixtures are cETLus listed for indoor damp locations. ADA

Warranty

Limited warranty: This fixture is free from defects in materials and workmanship for a period of 5 years from date of purchase.

Specifications and dimensions subject to change without notice.

LOCATION PREPARED BY COMMENTS CATALOG NUMBER DATE QUANTITY FIXTURE TYPE








Black/Copper

White/Silver



Ordering Information:

				Source				
Black/Copper		White/Silver	LED	Lumens	CCT	Н	W	D
SUMS	S051413L30D1BK	SUMS051413L30D1WH	20W	1300	3000K	14"	5"	3"
SUMS	SO51413L 30MVRK	SUMS0514131 30MVWH	20W	1300	3000K	14"	5"	3"