



LOCATION		DATE
PREPARED BY		QUANTITY
COMMENTS		FIXTURE TYPE
CATALOG NUMBER		

View LED Pendant VIP Series

Features

Frosted glass cylinder inside a clear glass cylinder suspended with a 9 ft. cord. Mounts to a standard junction box (not included).

Construction

The outer glass cylinder is 16" tall and 4-5/8" in diameter and the inner glass cylinder is 14" tall and 3-7/8" in diameter. The unit is held into place by three decorative studs. The canopy fits over a standard junction box. Power supply connections must be made inside a junction box (not included).

Finish

The canopy is plated in Satin Nickel.

Diffuser

Inner glass cylinder is 0.14" thick. Colors include cream (CR) and white (WH). Clear outer glass.

Electrical

D1 Driver

Direct wired with a constant current low voltage electronic LED driver rated at 120 VAC. The driver is dimmable with a 2-wire (Triac) or electronic low voltage (ELV) dimmer switch.

D2 Driver

Direct wired with a constant current low voltage electronic LED driver rated for 120-277 VAC. LED driver is dimmable 0-10V DC.

LED

All pendants include a 10W LED module. Light engine produces 1000 source lumens. 3000K or 4000K (CCT). 50,000 hr. LED life, 90 CRI.

Certification

All fixtures are ETL listed for indoor damp locations.

Warranty

Limited warranty: This fixture is free from defects in materials and workmanship for a period of 5 years from date of purchase.

Specifications and dimensions

subject to change without notice.



Ordering Information:

4-5/8" DIA. x 16" H

Series VIP	Source Lumens 1000	LED L	CCT 30 3000K 40 4000K	Driver D1 Voltage (120V TRIAC Dimming) D2 Voltage (120-277V 0-10V Dimming)	Finish SN Satin Nickel	Glass CR Cream WH White
----------------------	------------------------------	-----------------	------------------------------------	---	----------------------------------	--------------------------------------

Example: VIP1000L30D1SNCR