

Vasari LED Outdoor Sconce VSRW Series

Features

Die-cast aluminum housing with clear seeded glass diffuser. Provides down-light illumination. Ideal use in hallways, entrances or anywhere general lighting is needed. Provides lighting in residential, commercial and hospitality applications. Fixture mounts to standard junction box (not included).

Construction

Back plate is die-formed of 22-gauge steel. Standard mounting holes and hardware are included. Power supply connections must be made inside a junction box (not included).

Finish

Black powder coat finish.

Diffuser

Cleer seeded glass diffuser.

Electrical

Input 120 VAC / 60 Hz. Compatible with TRIAC and ELV dimmers. Minimum starting temp. -4° F / -20° C.

Lamping

Fixture includes a LED modules capable of producing: 12W = 1200 source lumens, 380 delivered lumens 18W = 1900 source lumens, 568 delivered lumens 3000K (CCT). Rated for 50,000 Hrs., 90 CRI.

Certification

All fixtures are cETLus listed for wet locations. Title 24/JA8 Compliant

Warranty

Limited warranty: This fixture is free from defects in materials and workmanship for a period of 5 years from date of purchase.

Specifications and dimensions subject to change without notice.

Ordering Information:

		Source	Delivered				
			Lumens	CCT	H	W	D
VSRW0412L30D1BK				3000K	11-3/4"	4"	4"
VSRW0517L30D1BK	18W	1900	568	3000K	17"	5-1/8"	5"

LOCATION	DATE
PREPARED BY	QUANTITY
COMMENTS	FIXTURE TYPE
CATALOG NUMBER	









