



Features

- High impact dynamic linear RGB wall washer
- Durable aluminum alloy housing with enamel finish and tempered glass lens are fully sealed for use in wet locations (IP65)
- Built-in driver and five foot grounded power cord simplify installation
- Integrated mounting holes in base/leg brackets with adjustable tilt design for installation flexibility
- 60,000 hours rated life

NOTE: To use WW-L48-RGB with previous RGB wall washers (LLW-RGB Series), item LW-WW-CONVERSION is needed for interconnection of signal cables (sold separately). Please contact American Lighting for more information

Available Finishes



Satin Aluminum

Listing / Ratings



Linear RGB Wall Washer

High power red, blue, and green LEDs combined with a durable aluminum housing rated for wet locations make this family of lighting tools perfect for high impact illumination, indoors or out. The Linear RGB fixtures must be powered directly with the attached five foot power cord, but allow data linking up to thirty fixtures.

Technical Information

| | |
|---------------|---|
| Series | WW-L48-RGB |
| Input Voltage | 120V AC, 60Hz |
| Wattage | 45W |
| Linkable | Up to 30 fixtures |
| Beam Angle | 25° |
| Dimmable | Via standalone features / DMX Controllers |
| Dimensions | 47.25"W x 5"H x 2-3/16"D |
| Mounting | Surface mount |
| Rating | IP65 (wet location) |
| Rated Life | 60,000 hrs |

Ordering Information

| | |
|--------------------|---|
| WW-L48-RGB | 48" Linear RGB Wall Washer |
| DMX-RGB-3 | 3-Channel DMX Controller |
| WW-EC15 | 15' Signal Cable |
| WW-END | Signal Termination End Cap |
| WW-XLR3 | 3ft DMX Adapter cable |
| WW-XLR3-15 | 15ft DMX Adapter cable |
| CUSTOMCABLE | DMX Adapter or signal cable (special order) |