



- Smart design helps reduce the effect of indoor allergens
- Lowest surface temperatures available perfect for homes with kids and pets
- Environmentally-friendly mineral oil retains heat much longer than regular baseboards, and spreads residual heat even after thermostat turns off
- Thermostat setpoint range 40° 85° F
- 120-volt grounded plug
- Sleep soundly, thanks to silent operation
- Includes high-temperature safety shutoff feature, and safety tip-over switch

Product Dimensions:

59" W x 9½" H x 6 ½" D 149.9 cm x 24.1 cm x 16.5 cm Ideal for bedrooms or nurseries, SoftHeat wraps your family in gentle, steady warmth that fills the room. Our portable version can be plugged into any standard 120-volt outlet.

ARCHITECTURAL - ENGINEERING INFORMATION

Heater is constructed of 22 gauge steel for durability and powder coated for a durable, smooth quality finish. Heater has a high temperature capillary thermal over load device that extends over the length of the heating element. Heater element is constructed of .875 inch diameter copper tubing and 2.375 inches x 2.375 inches aluminum fins mechanically bonded to the copper tube. Heating element is filled with a non-toxic engineered heat transfer fluid for maximum efficiency and thermal storage. Includes a built-in thermostat with OFF position and a grounded, 3-prong plug.

TECHNICAL INFORMATION

Baseboard heaters work best when placed near a window. Keep at least 12 inches minimum in front of baseboard and from objects hanging above (i.e., drapes).

Always plug heater directly into a properly grounded outlet. Heater may be placed directly on the floor with feet installed before first use.

In addition to the standard safety feature, 120 volt SoftHeat portable baseboards also have a built-in safety tip-over switch that stops electricity flowing to your heater if tipped over. Switch resets immediately upon heater standing upright.

UPC/PART	MODEL	DESCRIPTION	VOLTS	AMPS	WEIGHT (lbs/kg)
027418 13469 1	EPN1500W	SoftHeat portable baseboard, 1500 Watts, white	120	12.5	23.2 / 10.5





