

Eclipse LED Sconce ECPS Series

Features

White powder coated metal faceplate with a frosted acrylic diffuser. Indirect light for wall wash effect. Wall or ceiling mount. Ideal use in hallways, entrances, restrooms and anywhere general lighting is needed. Provides lighting in residential, commercial, and hospitality applications. Meets ADA requirements. Fixture mounts to standard junction box (not included).

Construction

Backplate is die formed 22-gauge steel and painted with lighting grade white. Standard mounting holes and hardware are included. Power supply connections must be made inside a junction box (not included).

Finish

All exposed metal is painted white powder coated finish.

Diffuser

Frosted white acrylic.

Electrical

Input 120-277 VAC 60 HZ. Compatible with residential (TRIAC/ELV) and commercial (0-10V) dimmers. TRIAC and ELV dimming only at 120 VAC.

Lamping

Fixture includes an LED module producing: 12W = 730 delivered lumens 16W = 988 delivered lumens Adjustable 2700K, 3000K, 3500K, 4000K, 5000K (CCT). Rated for 50,000 Hrs., 90 CRI.

Certification

All fixtures are cETLus listed for indoor damp locations. Title 24/JA8 Compliant ADA Compliant

Warranty

Limited warranty: This fixture is free from defects in materials and workmanship for a period of 5 years from date of purchase.

Specifications and dimensions subject to change without notice.

Ordering Information:

		Delivered				
White	LED	Lumens	Adjustable CCT	DIA.	D	
ECPS0606LAJUDWH	12W	730	2700K/3000K/3500K/4000K/5000K	6"	2"	
ECPS0909LAJUDWH	16\//	988	2700K/3000K/3500K/4000K/5000K	9"	2"	

LOCATION	DATE
PREPARED BY	QUANTITY
COMMENTS	
	FIXTURE TYPE
CATALOG NUMBER	











