



	<b>NE2134Z</b>	<b>LBP</b>	<b>115V</b>	<b>134a</b>
<b>Specifications</b> Approximate H. P. 1/2 Starting Torque High Refrigerant 134a Evaporator Temperature Low Evaporator Temperature -22° to 23°F			<b>Usage</b> Drinking Water Coolers Dehumidifiers Ice Machines Reach In Refrigerators Beer Coolers	

<b>LBP Performance</b>					
<b>Temperature °F</b>	-22	<b>-10</b>	5	14	23
<b>Capacity BTU/Hr</b>	953	<b>1,450</b>	2,134	2,688	3,349
<b>Power W</b>	285	<b>346</b>	434	492	555
<b>Current Amps</b>	5.02	<b>5.3</b>	5.85	6.24	6.69
<b>Temperature °C</b>	-30	<b>-23.3</b>	-15	-10	-5
<b>Capacity Kcal/Hr</b>	240	<b>365</b>	538	677	844

<b>LBP Rating</b>	<b>ASHRAE</b>	<b>Rating Point (Bolded above)</b>	<b>HBP Rating</b>	<b>ASHRAE</b>
Condensing	130°F		Condensing	N/A
Evaporator	-10°F		Evaporator	N/A
Return Gas	90°F		Return Gas	N/A
Ambient	90°F		Ambient	N/A
Liquid Temp.	90°F		Liquid Temp.	N/A

<b>Material</b>	<b>Part number</b>	<b>Description</b>	<b>Compressor Cross Ref.</b>
Compressor	262JG92	NE2134Z	Model            Appl.
Relay	2271011	9660C-3018-183	AEA2413YXA    LBP, HST
Overload	2324063	T0590/J5	
Start Cap	2252320	189-227 mfd / 165V	
Grommet	2221003		
Sleeve	2222015		

**EMBRACO NORTH AMERICA, INC.**  
 2800 Vista Ridge Dr. Suite 100, Suwanee Ga, 30024 Phone: 678-804-1337