

2" SnapTrim Adjustable Downlight



EnVision LED has developed a 2" LED Downlight, available in a straight or adjustable version, that eliminates the need for a can. The external remote junction box mounts inside the ceiling and the fixture is IC rated. EnVisions 2" downlight features a deep architectural 1.5" baffle reflector that reduces glare and eliminates hot spots. By reducing material cost and installation time, the EnVision SnapTrim is the ideal retrofit or new construction recessed lighting solution yet. Simply cut a hole in the ceiling, power the J-Box to the wall switch and "snap" the trim flush.



Detail Specification:

- Wet Location Rated
- CRI 90 COB LED Chip, R9>50
- 12V Electronic Constant Voltage Transformer Must be Used
- 35° Tilt
- 360° Rotation
- Operating Temperature: 0°F ~ +113°F
- PF >0.9
- Triac and ELV Dimmable Down to 5%
- Wire Length: Total length with adapter 12.5"

Applications:

- Residential or Commercial Lighting
- New Construction or Remodel Use
- General Recessed Lighting

Product Information:

- Di-cast aluminum housing for better heat dissipation
- Available in white, black
- SnapTrim Vanless: Spring clips with j-box eliminates can
- L70 @ 50,000 Hours lumen maintenance

Mounting:

- No can needed in remodel applications, tension clip springs clamp into 1/2" to 1.5" thick ceiling
- Pre-wired junction box with circuit wiring built in (3 inc / 3 out)
- New construction rough-in plate or mounting plate with joist bars available

Certifications:

- ETL Listed for USA and CA
- Energy Star Certified
- IC Rated and ASTM-E283 Air-Tight
- CA Title 24 JA8-2019 CEC Listed
- FCC CFR 47, FCC Part 15, Subpart B:2017
- 5 Year EnVision LED Limited Warranty

What's Included:

- LED Fixture
- Installation Guide
- Cut Out Template

LED-DLJBX-ADJ-2-5W-30K-12V-6

1 Product	2 Size	3 Watts	4 Color	5 Voltage	6 Finish
LED-DLJBX-ADJ	2 2 Inches	5W 350lm	30K 3000K	12V 12 Volts	WH White BLK Black

Specs and model numbers are subject to change with or without notice.

FEATURES



DIMENSIONS



OPTIONAL ACCESSORIES



Constant Voltage Triac Dimmable Transformers

Model	Voltage	Watts
CV-12V-DC-20W-DIM	Input: 120-277V Output: 12V DC	20w
CV-12V-DC-60W-DIM	Input: 120-277V Output: 12V DC	60w
CV-12V-DC-150W-DIM	Input: 120-277V Output: 12V DC	150w
CV-24V-DC-60W-DIM	Input: 120-277V Output: 24V DC	60w



Electronic Magnetic Transformers

Model	Input Voltage	Output Voltage	Watts
MLE-12V-DC-30W-DIM	120VAC	12V	30w
MLE-12V-DC-60W-DIM	120VAC	12V	60w
MLE-12V-DC-80W-DIM	120VAC	12V	80w
MLE-12V-DC-120W-DIM	120VAC	12V	120w
MLE-12V-DC-150W-DIM	120VAC	12V	150w
MLE-12V-DC-200W-DIM	120VAC	12V	200w
MLE-12V-DC-300W-DIM	120VAC	12V	300w