

Project:	
Part#:	
Type:	



3" Regressed Downlight Selectable CCT: 27/30/35/40/50K

EnVision LED has developed a line of 3" LED Regressed Adjustable Downlight that eliminates the need for a can. The external remote junction box mounts inside the ceiling and the fixture is IC Rated. EnVisions 3" downlight features a trim-changable module. Trim changing accessories include: bronze round and square, black round and square, and white square. Now available with 5CCT color changing technology, select from 27K, 30K, 35K, 40K, and 50K with the flick of a switch!

- **Detail Specifications:** • IP65 Wet Location Rated
- CRI 93 COB LED Chip, R9>50
- 120V Driver
- 40° Beam Angle
- Operating Temperature: 0°F ~ +113°F
- PF > 0.9
- Cut Out Dimension: 3-3/8"
- Triac and ELV Dimmable down to 5%

Applications:

- Residential or Commercial Lighting
- New Construction or Remodel use
- General recessed lighting

Product Information:

- 5CCT Selectable: 27/30/35/40/50K
- Available in white or black round finish
- SnapTrim Canless: Spring clips with j-box eliminates can
- Optional Emergency Backup Available: delivers full lumens in EM mode
- L70 @ 50,000 Hours lumen maintenance

Mounting:

- No can needed in remodel applications, tension clip springs clamp into 1/2" to 1.5" thick ceiling
- · Pre-wired junction box with circuit wiring built in (3 in / 3 out)
- New construction rough-in plate or mounting plate with joist bars available (See accessories listed below)

Certifications:

- ETL Listed for USA and CA
- Energy Star Certifies
- IC Rated and ASTM-E283 Air-Tight
- CA Title 24 JA8-2019 CEC Listed
- FCC CFR 47, FCC Part 15, Subpart B:2017
- 5 Year EnVision LED Limited Warranty

- Whats Included?:
- LED Module
- Mounting Screws
- Junction Box
- Installation Guide
- Cut Out Template



Specs and model numbers are subject to change with or without notice













FEATURES

Easy Installation

Simply snap downlight into the hole that has been cut into ceiling for an easy install.

High Quality LEDs

50,000 hour life with a 40° beam angle make these downlights perfect for any construction project.

5CCT Selectable

Slide switch on wire or driver to choose between 27/30/35/40/50K color temps.

Dimmable

Set the mood right with a 5-100% dimming light, which is compatible with most TRIAC/ELV dimmers.

Detachable Color Trims

Choose between a selection of different changable trims, between round or square black, bronze, and white square.

Hole Cut Size **3**3/8" (79.38mm)



3" Regessed Downlight

Selectable CCT: 27/30/35/40/50K

OPTIONAL ACCESSORIES



CUNV-NC-ICAT

New Construction Plate

Makes new construction installation easier. Universal plate compatible for 2", 4", 6" trims with J-Boxes.



C4-JBX-RI 4" Rough-In Plate

Make installation even easier with this rough-in plate.



JBX-JUMP-(4'/10'/20')

Connector Extension Cord

Extension cord in between driver and downlight. Available in 4', 10', 20' lengths.

Accessory Model	Description		
CUNV-NC-ICAT	2/4/6" New Construction Plate		
C4-JBX-RI	4" Rough-In Plate		
JBX-JUMP-4'	4' Connector Extension Cord		
JBX-JUMP-6'	6' Connector Extension Cord		
JBX-JUMP-10'	10' Connector Extension Cord		

DIMMER COMPATIBILITY						
Brand	Series	Model	Load	Dimmability		
Lutron	Ariadni	AYCL-153P	150W	OK		
	Diva	DV-600PR	600W	OK		
	Diva	DVCL-153P	150W	OK		
	Maestro	MACL-153MH	600W	OK		
	Maestro Wireless	MRF2-6CL	150W	OK		
	Rotary	D-600P	600W	OK		
	Electronic(ELV)	NTELV-300P	600W	OK		
	Skylark	S-600P	600W	OK		
	Skylark Contour	CT-600P	600W	OK		
	Skylark Contour	CTCL-153P	150W	OK		
	Toggler	TG-600P	600W	OK		
	Toggler	TGCL-153P	150W	OK		
Leviton	Sureslide	6633	600W	OK		
	Sureslide Decora	6674	600W	20-100%		
	Trimatron	6602	600W	20-100%		
	ILLVMATECH	IPL06	600W	OK		
Legrand	Adorne	ADTP703TU	700W	20-100%		
	Harmony	H703PTW	700W	OK		
Cooper	Aspire	9540	1000W	OK		
	Devine	DAL06P	300W	OK		

DIMENSIONS



