

Project: \_\_\_\_\_  
 Part#: \_\_\_\_\_  
 Type: \_\_\_\_\_

# 8FT T8 Glass Frosted Type A+B (2 Piece)

The NEW EnVision LED T8 8FT Bulb can be installed with the existing ballast (see list) or double ended ballast bypass. Our revolutionary design features two four foot pieces that connect together making transportation easier and more cost efficient. EnVision has added a safety feature by using a protective shatterproof film on all of our tubes. Now available in 8ft, detachable into two 4ft fixtures, save money on shipping and space in storage.

### Applications:

- Fluorescent Retrofitting
- New Construction
- Warehouse Lighting
- Commercial Lighting

### Product Information:

- Industry changing 2 piece 4ft design
- Quality components that pass UL 1993 current leakage
- Hybrid: Compatible Type A+B with or without ballast
- Pin Changeable: Includes single pin FA8 with optional R17D pin

### Why pick the EnVision T8?:

- Average life (L70) of 50,000 hours with chips that are tested with LM-79 and LM-80 compliance.
- T8 Bulb is tested 120 hours before being boxed and shipped.
- Light beam spread replicates the same look as a fluorescent, but with improved light output and efficiency.
- 5 Year Warranty\*

**LED - T8 - DF - 8FT - 42W -** **Color** - **Accessories** - **Warranty**  
3 4 5

1	Product	2	Wattage	3	Color	4	Accessories	5	Warranty
LED-T8-DF-8FT	8FT T8 Glass Frosted Type A+B (2 Piece)	42W	42W (5,500lm)	40K 50K	4000K 5000K	(Blank) R17D-EC	FA8 Single Pin (Included) R17(D) End Cap Converter (Switchable end cap for 8ft Tube)	(Blank) 10YR	5 Years (incl.) 10 Years

*Specs and model numbers are subject to change with or without notice*

**FEATURES****Easy for Stocking**

Two piece design enables bulbs to come in a 4FT package

**Magnetic Clip**

Magnetic clip that supports the middle of the bulb to eliminate bending

**Pins**

Includes single pin FA8  
R17D pin is optional and changeable

**Leakage Protection**

Passed UL1993 new standard with current leakage protection

**Type A+B**


Works with existing ballast or bypass double sided connection

**2 Piece Design**


Easily put together the two 4ft pieces




**PHOTOMETRICS**




**40K**



**50K**




**40K**




**50K**

**WIRING DIAGRAM**

Type A (Ballast Compatible) Assembly introduction:



Type B (AC directly, double end ballast bypass) Assembly introduction:



**Ballast Compatibility List**

**RISK OF FIRE:** Check the ballast compatibility list before installing this retrofit kit to the fixtures with electronic ballast. DO NOT install this kit to the fixture if the ballast is not on this list. In this instance, please bypass the ballast or confirm with the supplier

No. Ballast Brand	Model No.
GE	GE259MAX-G-N
GE	GE259MAX-G-N-DIYB
OSRAM SYLVANIA	QHE 2X59T8/UNV ISL-SC
OSRAM SYLVANIA	QTP 2X59T8/UNV ISL-SC