

1007-XP-150-CART-515-6P

1007-XP-150 LED WORKLIGHT CART w/100 FT 14/3 BLK SOOW AND NEMA 5-15P WT PLUG



Key features



- cETLus listed lamp
- Heavy duty, light weight, spark resistant aluminum frame
- Bolt on lifting eyes (Optional)
- Cord management bracket
- Class I, Division 1, Groups C, D
- Class I, Division 2, Groups A,B,C,D
- Class II, Division 1, Groups E,F,G
- Class II, Division 2, Groups E,F,G
- Class III
- NEMA 4X, IP66
- T3 temperature rating
- High efficacy: up to 140lm/W
- CRI>70
- Copper free aluminum
- High vibration resistance
- Ambient temperature range: -40°C to 60°C

Ideal Application

Portable Mobile Lighting for Oil & Gas Industries, Distilleries, Paint Manufacturing, Pumping Stations, Mining, Vessel Lighting, High Humidity Areas, High Temperature Locations

Color

Gray

UPC Code

782862926536

Country of Origin

USA

Specifications

Brand	Ericson
Sub Brand / Trademark	Hi-Bay XP on Cart
Category	Hazardous Location Grade
Sub Category	Wide Area Light

Technical Info

Bulb Type	LED
Lumens	21000
Cable Length	100
Cable	14/3
Cable Type	SOW
Max Amps	1.2
Max Volts	120
Max Watts	150
Primary Cable End	NEMA 5-15 (1510-PW6P) Water Tight Plug
NEMA Environment	Class I Division 1, Groups C, D • Class I Division 2, Groups A, B, C, D • Class II Division 1 & 2, Groups E, F, G • Class III
Construction	Cast Aluminum & Welded Aluminum Cart

Standards & Certifications

ETL	ETL Listed Luminaire
cETL	cETL Listed Luminaire

Shipping & Logistics Info

Pack/Unit Qty	1
HTS code	9405106020
ECCN	EAR99
Gross Weight (lbs)	120.00000
Shipment Packaging Length (in)	26
Warranty	1 Year



Ericson Manufacturing Company
4323 Hamann Parkway
Willoughby, OH 44094, USA



1-800-374-2766
info@ericson.com

ericson.com