

1007-XP-80

BAYLIGHT, EXPLOSION PROOF C1D1 80W LED 11200LM
5000K NO REFLECTOR 120 DEGREE BEAM w/TRUNNION



Key features



DESIGN BUILD



- High efficacy: up to 140lm/W• CRI>80• Surface and pendant mounting• Copper free aluminium• High vibration resistance• 5 year warranty• Ambient temperature range: -40°C to 60°C

Ideal Application

Oil & Gas Industries, Distilleries, Paint Manufacturing, Pumping Stations, Mining, Vessel Lighting, High Humidity Areas, High Temperature Locations

Color

Gray

UPC Code

782862906590

Country of Origin

CHINA

Specifications

Brand	Ericson
Sub Brand / Trademark	Hi-Bay XP
Category	Hazardous Location Grade
Sub Category	High Bay Light

Technical Info

Bulb Type	LED
Cable Length	3
Cable	16/3
Cable Type	SJTW
Max Amps	0.7
Primary Cable End	Blunt End
NEMA Environment	Class I, Division 1 & 2, Groups C,D,F &G
Construction	Cast Aluminum

Standards & Certifications

ETL	ETL Listed
cETL	cETL Listed

Shipping & Logistics Info

Pack/Unit Qty	1
HTS code	9405408410
ECCN	EAR99
Gross Weight (lbs)	12.00000
Shipment Packaging Length (in)	14.37
Warranty	1 Year



Ericson Manufacturing Company
4323 Hamann Parkway
Willoughby, OH 44094, USA



1-800-374-2766
info@ericson.com

ericson.com