

Oscar™ Series 50 Amp Power Distribution Units

1066, 1066-B, 1066FS, 1066FS-3, 1066-BFS, 1067-LC,
1067-BLC, 1067-ALC, 1067-CLC



UNIT PROVIDES BOTH GFCI AND
OPEN NEUTRAL PROTECTION



1066, 1066-B

HEAVY-DUTY, SAFETY YELLOW
POWDER-COATED ENCLOSURE



1066FS, 1066-BFS

HEAVY-DUTY POWDER-COATED
STEEL SKID LEGS

WEATHER RESISTANT
COVERS



1066FS-3

UNIT PROVIDES BOTH GFCI AND
OPEN NEUTRAL PROTECTION

WEATHER RESISTANT
COVERS



1067-LC, 1067-BLC, 1067-ALC 1067-CLC



Standard Safety Features:

- cETLus listed for use in U.S. and Canada
- Built to UL1640 safety standards
- Heavy-duty, safety yellow powder-coated enclosure
- Outdoor units provide NEMA 3R weather resistance protection for circuitry
- Automatic power-up GFCIs are ready immediately. Only need to push reset after a trip
- Heavy-duty powder-coated steel skids to insure rugged, dependable job site performance

- Select models offer weather resistant covers protect circuit breakers and receptacles from damage & weather
- CS6375 50Amp, 125/250V power inlet
- Power inlet/outlet clearly marked on lid for quick identification
- Unit has feed-thru capability to daisy-chain multiple units.
- Unit is field repairable by qualified personnel. Parts list and wiring diagram appear on underside of lid
- Net weight of 34 pounds
- Product dimensions of 22.5”L x 16.25”W x 11.75”H

Applications:

- Public Events
- Convention Centers
- General Maintenance
- Stadiums
- Industrial Construction
- Commercial Construction

Selection Guide

Main Features

Catalog Number	50A inlet and feedthrough	Environmental Rating	20 A Outlets	30 A Outlet	30 A Outlet GFCI Circuit Breaker
Straight blade NEMA 5-20, 3 circuit, 6 duplex receptacles					
1066FS-3	50A 125/250V CS Style	Outdoor rated, NEMA 3R, with Weather Resistant Covers	(6) NEMA 5-20 Duplexes, with (3) GFCI modules, (3) 20A C.B.	(1) NEMA L6-30, with (1) 2 pole 30A C.B.	NO
Straight blade NEMA 5-20, 6 circuit, 6 duplex receptacles					
1066	50A 125/250V CS Style	Indoor Rated, No W.R. Covers	(6) NEMA 5-20 Duplexes, with (6) GFCI modules, (6) 20A C.B.	(1) NEMA L6-30, with (1) 2 pole 30A C.B.	NO
1066-B	50A 125/250V CS Style	Indoor Rated, No W.R. Covers	(6) NEMA 5-20 Duplexes, with (6) GFCI modules, (6) 20A C.B.	(1) NEMA L6-30, with (1) 2 pole 30A GFCI C.B.	YES
1066FS	50A 125/250V CS Style	Outdoor rated, NEMA 3R, with Weather Resistant Covers	(6) NEMA 5-20 Duplexes, with (6) GFCI modules, (6) 20A C.B.	(1) NEMA L6-30, with (1) 2 pole 30A C.B.	NO
1066-BFS	50A 125/250V CS Style	Outdoor rated, NEMA 3R, with Weather Resistant Covers	(6) NEMA 5-20 Duplexes, with (6) GFCI modules, (6) 20A C.B.	(1) NEMA L6-30, with (1) 2 pole 30A GFCI C.B.	YES
Straight blade NEMA 5-20, 6 circuit, 6 single receptacles					
1067-LC	50A 125/250V CS Style	Outdoor rated, NEMA 3R, with Weather Resistant Covers	(6) NEMA 5-20 Single, with (6) GFCI modules, (6) 20A C.B.	(1) NEMA L6-30, with (1) 2 pole 30A C.B.	NO
1067-BLC	50A 125/250V CS Style	Outdoor rated, NEMA 3R, with Weather Resistant Covers	(6) NEMA 5-20 Single, with (6) GFCI modules, (6) 20A C.B.	(1) NEMA L6-30, with (1) 2 pole 30A GFCI C.B.	YES
Twist Lock NEMA L5-20, 6 circuit, 6 single receptacles					
1067-ALC	50A 125/250V CS Style	Outdoor rated, NEMA 3R, with Weather Resistant Covers	(6) NEMA L5-20 Singles, with (6) GFCI modules, (6) 20A C.B.	(1) NEMA L6-30, with (1) 2 pole 30A C.B.	NO
1067-CLC	50A 125/250V CS Style	Outdoor rated, NEMA 3R, with Weather Resistant Covers	(6) NEMA L5-20 Singles, with (6) GFCI modules, (6) 20A C.B.	(1) NEMA L6-30, with (1) 2 pole 30A GFCI C.B.	YES

Accessory Selection Guide:

Catalog Number	Description	Image Reference
63DSO/63BSO	Cord set, 100' or 50' #6/3-8/1 SOOW 50A 125V/250V	A
SR50	Power outlet receptacle in weatherproof box with lift cover and 24" leads 50A, 125V/250V	B
63YSTW	50 Amp "Y" adapter	C
I23B	50 ft. 20 Amp cord sets, molded NEMA 5-15 plug and connector	D
I23D	100 ft. 20 Amp cord sets, molded NEMA 5-15 plug and connector	D
I23B-TT	50 ft. 20 Amp cord set, molded tri-tap	D
I23D-TT	100 ft. 20 Amp cord sets, molded tri-tap	D



Ericson Manufacturing Company
4323 Hamann Parkway
Willoughby, OH 44094, USA



1.800.374.2766
info@ericson.com
www.ericson.com
L1000199G