

330BA6S

IEC 309 PIN & SLEEVE ANGLED INLET, 30A 250V 1PH 2P/3W,
SPLASH PROOF (IP44)



Key features



EXPRESS BUILD



Ideal Application

Splash-proof (IP44) devices are suitable and recommended for use in a variety of light industrial environments and provide complete protection against contact with live parts, damaging deposits of dirt and dust and splashing water. Splashproof devices provide many of the heavy duty construction features found in the watertight products, but at a more economical cost

Color

Blue & Gray

UPC Code

782862931646

Country of Origin

USA

Specifications

Brand	Ericson
Sub Brand / Trademark	IEC 309
Category	Wiring Devices
Sub Category	IEC - Splash Proof

Technical Info

Device Type	Inlet
Blade Style	6 = Female Ground Clock Position
NEMA Configuration	IEC 309 Pin & Sleeve
Amps	30
Voltage	250
Phase	1
Poles / Wires	2P/3W
WD_CSConfig_c	Angled
Environmental Rating	Splash proof (IP44), IP44

Standards & Certifications

UL	Listed to UL1682
cUL	Certified to CSA-C22.2 No. 182.1

Shipping & Logistics Info

HTS code	8536694020
ECCN	EAR99
Gross Weight (lbs)	0.00000
Shipment Packaging Length (in)	4
Warranty	1 Year



Ericson Manufacturing Company
4323 Hamann Parkway
Willoughby, OH 44094, USA



1-800-374-2766
info@ericson.com

ericson.com