

HL11-16325YS- 1-DLV-XFMR

HANDLAMP, LOW VOLTAGE LED W/ SWITCH W/ 25FT OF
16/3 SOW CABLE W/ INLINE XFMR & NEMA 5-15 WATER
TIGHT PLUG



Key features



Standard Features:

- High impact, shatter-proof tube with replaceable frosted tube shield
- Beam angle available in 200° and 360°
- Wired with 15A, 125V, watertight plug
- Driver range of 100-277 volts at 50/60 Hz
- Environmental rating: Suitable for outdoor use in wet locations

Optional Features:

- Replaceable clear tube shield protector
- Handle switch available on HL06 and HL11 models - Add HS
- Other NEMA plug, configurations available
- Custom cable color and printing available
- Can be included with cable reel applications
- Contact Ericson for custom configurations

Ideal Application

A hand held or hanging task light that is required for Maintenance ops, confined space entry, Aerospace, Ship building, Petrochem, Powergen, Mining, Emergency Response and Military applications.

Color

Black

UPC Code

782862928035

Country of Origin

USA

Specifications

Brand	Ericson
Sub Brand / Trademark	HL
Category	Industrial Grade
Sub Category	Hand Lamp - Low Voltage

Technical Info

Bulb Type	LED
Lumens	1440
Cable Length	25
Cable	16/3
Cable Type	SOW
Max Amps	0.15
Max Volts	120
Max Watts	15
Primary Cable End	INLINE XFMR & NEMA 5-15 (1510-PW6P) Water Tight Plug
NEMA Environment	Outdoor Use, Wet Location
Finish	Non-conductive molded endcaps with shatter resistant polycarb LED tube.
Construction	Industrial grade, LED handlamp designed for rugged environments

Shipping & Logistics Info

Pack/Unit Qty	1
HTS code	8539490080
ECCN	EAR99
Gross Weight (lbs)	4.80000
Shipment Packaging Length (in)	24
Warranty	1 Year



Ericson Manufacturing Company
4323 Hamann Parkway
Willoughby, OH 44094, USA



1-800-374-2766
info@ericson.com

ericson.com