
WL11-16325Y-1-360











• High impact, shatter-proof tube with replaceable frosted tube shield• Beam angle available in 200° and 360°• Bi-directional version offers glare protection to prevent eye strain• Wired with 15A, 125V, water-tight plug & feed-thru water-tight connector• Driver range of 100-277 volts at 50/60 Hz• Environmental rating: Suitable for outdoor use in wet locations

| Ideal Application | Overhead Task Lighting required for Maintenance ops, confined space entry, Aerospace, Ship building, Petrochem, Powergen, Mining, Emergency Response and Military applications. |
|-------------------|--|
| Color | Yellow |
| UPC Code | 782862927748 |
| Country of Origin | USA |

Specifications

| Brand | Ericson |
|-----------------------|------------------|
| Sub Brand / Trademark | WL |
| Category | Industrial Grade |
| Sub Category | Work Lamp |

Technical Info

| Bulb Type | LED OMNI |
|---------------------|--|
| Lumens | 1800 |
| Cable Length | 25 |
| Cable | 16/3 |
| Cable Type | SOW |
| Max Amps | 13 |
| Max Volts | 120 |
| Max Watts | 1560 |
| Primary Cable End | NEMA 5-15 (1510-PW6P) Water Tight Plug |
| Secondary Cable End | NEMA 5-15 (1610-CW6P) Water Tight Connector |
| NEMA Environment | Outdoor Use, Wet Location |
| Finish | Non-conductive molded endcaps with shatter resistant polycarb LED tube. |
| Construction | Industrial grade, LED overhead worklamp designed for rugged environments |

Shipping & Logistics Info

| Pack/Unit Qty | 1 |
|--------------------------------|------------|
| HTS code | 9405408440 |
| ECCN | EAR99 |
| Gross Weight (Ibs) | 4.80000 |
| Shipment Packaging Length (in) | 20 |
| Warranty | 1 Year |



Ericson Manufacturing Company 4323 Hamann Parkway Willoughby, OH 44094, USA



1-800-374-2766 info@ericson.com ericson.com